

9 Conclusions

The goal of this thesis has been to show that the use of change identifiers will reduce the time taken to maintain a footprint over a dynamic dot pattern while introducing an acceptable level of error.

The inquiry began with an investigation of the dot patterns. Our goal was, not merely to provide background to the change identifiers, but to see if measurements on the dot patterns could provide useful information in its own right. This exploration of the dot patterns led to the identification and analysis of the dot pattern descriptors. There is a wealth of information present in the individual patterns and the descriptors are measures of this data. It was found that, not only, could the descriptors provide an stable base for the change identifiers but that they may be able give a classification structure for the dot patterns. A preliminary examination of how this classification might be constructed is demonstrated in Chapter 10.

Footprints have a large scope of operation; appearing in different forms across a range of fields. Before looking at the change identifiers this thesis devoted a chapter (Chapter 4) to the investigation of the types of footprint that are commonly produced by the footprint algorithms in the literature and proposed a classification (as an extension of the work performed in [21]) based on this investigation. The chapter also looked at how the footprint type may be affected as it is updated over a dynamic dot pattern; further discussion on which can be found within the future work chapter.

Having discussed the underlying aspects of the proposed problem the thesis examined the change identifiers in greater detail. Chapter 5 presented the change identifiers used within this thesis and proposed a method with which to combine them into sets measuring multiple different types of change. It also introduced an assessment approach based on comparing the stored footprint the change identifier set presented at any particular dot pattern phase with the ‘true’ footprint, i.e. the footprint that would have been created had the algorithm been run for the phase.

With the change identifiers defined and an assessment method in place the experimentation could be performed. The results of these were shown in Chapter 7, which also detailed the range of dynamic dot patterns and algorithms that were used to provide a fair appraisal of the change identifier sets’ worth. Chapter 7 showed that it was possible to reduce (greatly in some instances) the number of footprint updates while maintaining a symmetric area difference that was low proportional to the area of the ‘true’ footprint. The chapter also demonstrated that some identifier sets can out-perform others for specific patterns and that it is possible to create sets to do so using knowledge about the dynamic dot pattern’s

nature. Finally the results indicated that some identifiers may be generally more applicable than others.

Choosing the appropriate set for any given application is the main difficulty that may arise when using them. For some applications it may be easy to know in advance what type of change is most likely to occur and therefore which identifiers to use, however there are some applications in which the change can occur in different and unpredictable ways. In such erratic cases we need to find a set of identifiers which can identify a mixed range of change types while still making time savings. The chapter on change identifier set selection Chapter 8 undertook this search using Multi-Objective Optimisation techniques which converged on some identifiers that were generally applicable to the test data used. It was noted, however, that this did not indicate that these identifier were superior to others, but that they are useful in many situations. The chapter also compared the generally applicable sets with a set created using knowledge about a dynamic dot pattern to confirm the statement within the results chapter that a human can create effective sets without needing to perform large scale analysis of the dynamic dot pattern.

This thesis has presented the concept of change identifiers and shown that they can be used to reduce the number of footprint updates required to have a suitable representation of a dynamic dot pattern with a user controllable error trade-off. It has provided an initial set of change identifiers and a framework in which they can be used. Further to the use of change identifiers as a way of reducing the number of updates other uses they might have were explored. This exploration led to the conclusion that the information supplied by the change identifiers could well be useful in its own right, perhaps even by-passing the need to produce a footprint in many cases (for example when it only needs to be known if the extent is increasing).

We conclude that the change identifiers are a useful and novel approach to the examination of dynamic dot patterns and that they have scope for use beyond that presented here. We make this statement while aware that there is certainly need for more testing over real world data and note with interest the forthcoming workshop to be chaired by Dr Antony Galton and Dr Zena Wood (Understanding and Modelling Collective Phenomena) which will hopefully provide more examples of such data.

Bibliography

- [1] A.G.Hamilton. *Linear Algebra – An Introduction With Concurrent Examples*. Cambridge University Press, 1994.
- [2] H. Alani, C. B. Jones, and D. Tudhope. Voronoi-based region approximation for geographical information retrieval with gazetteers. *International Journal of Geographical Information Science*, 15(4):287–306, 2001.
- [3] Walid Ali and Bernard Moulin. 2d-3d multiagent geosimulation with knowledge-based agents of customers shopping behavior in a shopping mall. In AnthonyG. Cohn and DavidM. Mark, editors, *Spatial Information Theory*, volume 3693 of *Lecture Notes in Computer Science*, pages 445–458. Springer Berlin Heidelberg, 2005.
- [4] Natalia Andrienko and Gennady Andrienko. Designing visual analytics methods for massive collections of movement data. *Cartographica*, 42(2):117–138, 2007.
- [5] Avi Arampatzis, Marc van Kreveld, Iris Reinacher, Christopher B. Jones, Subodh Vaid, Paul Clough, Hideo Joho, and Mark Sanderson. Web-based delineation of imprecise regions. In *Computers, Environment and Urban Systems*, volume 30, pages 436–459. Elsevier, 2006.
- [6] Julien Basch, Leonidas J. Guibas, and John Hershberger. Data structures for mobile data. In *Proceedings of the eighth annual ACM-SIAM symposium on Discrete algorithms*, SODA '97, pages 747–756, Philadelphia, PA, USA, 1997. Society for Industrial and Applied Mathematics.
- [7] R. Bayer and E. M. McCreight. Organization and maintenance of large ordered indexes. *Acta Informatica*, 1:173–189, 1972.
- [8] Marc Benkert, Joachim Gudmundsson, Florian Hübner, and Thomas Wolle. Reporting flock patterns. *Computational Geometry - Theory and Applications*, 2007.
- [9] Brandon Bennett, Derek R. Magee, Anthony G. Cohn, and David C. Hogg. Enhanced tracking and recognition of moving objects by reasoning about spatio-temporal continuity. *Image and Vision Computing*, 26(1):67–81, January 2008.
- [10] Mark de Berg, Otfried Cheong, Marc van Kreveld, and Mark Overmars. *Computational Geometry, Algorithms and Applications*. Springer, third edition, 2008.
- [11] Christopher M. Bishop. *Pattern Recognition and Machine Learning*. Springer, 2007.
- [12] D. Black. *Investigation of the possible increased incidence of cancer in West Cumbria: report of the Independent Advisory Group*. H.M.S.O., 1984.

- [13] P. Bogaert, N. Van de Weghe, A.G. Cohn, F. Witlox, and P. De Maeyer. Reasoning about moving point objects on networks. In M Raubal, J H Miller, U A Frank, and F Goodchild, editors, *4th International Conference on Geographic Information Science (GIScience 2006)*, 2006.
- [14] A. Ray Chaudhuri, B. B. Chaudhuri, and S. K. Parui. A novel approach to computation of the shape of a dot pattern and extraction of its perceptual border. In *Computer Vision and Image Understanding*, volume 68, pages 257–275. Academic Press, 1997.
- [15] Yi-Jen Chiang and Roberto Tamassia. Dynamic algorithms in computational geometry. In *Proceedings of the IEEE*, volume 80, pages 1412–1434, 1992.
- [16] Kalyanmoy Deb. *Multi-Objective Optimization using evolutionary Algorithms*. Wiley, 2001.
- [17] Géraldine Del Mondo, John G. Stell, Christophe Claramunt, and Rémy Thibaud. A graph model for spatio-temporal evolution. *Journal of Universal Computer Science*, 16(11):1452–1477, 2010.
- [18] Matthias Delafontaine, Anthony G. Cohn, and Nico Van de Weghe. Implementing a qualitative calculus to analyse moving point objects. *Expert Systems with Applications*, 38(5):5187–5196, 2011.
- [19] Somayeh Dodge, Robert Weibel, and Anna-Katharina Lautenschitz. Towards a taxonomy of movement patterns. *Information Visualization*, 7(3-4):240–252, 2008.
- [20] Matt Duckham, Lars Kulik, Mike Worboys, and Antony Galton. Efficient generation of simple polygons for characterizing the shape of a set of points in the plane. In *Pattern Recognition*, volume 41, pages 3224–3236. Elsevier, 2008.
- [21] Max Dupenois and Antony Galton. Assigning footprints to dot sets: An analytical survey. In K. S. Hornsby, C. Claramunt, M. Denis, and G. Ligozat, editors, *Spatial Information Theory: Proceedings of the 9th International Conference COSIT 2009*, pages 227–244, Berlin, 2009. Springer.
- [22] H. Edelsbrunner. Weighted alpha shapes. Technical Report UIUCDCS-R-92-1760, Department of Computer Science, University of Illinois, 1992.
- [23] Herbert Edelsbrunner, David G. Kirkpatrick, and Raimund Seidel. On the shape of a set of points in the plane. In *Computer Vision and Image Understanding*, volume IT-29, pages 551–559. IEEE, 1983.
- [24] Herbert Edelsbrunner and Ernst P. Mücke. Three-dimensional alpha shapes. In *Proceedings of the 1992 workshop on Volume visualization*, VVS '92, pages 75–82. ACM, 1992.
- [25] Max Egenhofer and Robert Franzosa. Point-set topological spatial relations. *International Journal of Geographical Information Systems*, 5(2):161–174, 1991.
- [26] Antony Galton. *Qualitative Spatial Change*. Oxford University Press, 2000.

- [27] Antony Galton. Pareto-optimality of cognitively preferred polygonal hulls for dot patterns. In *Spatial Cognition*, 2008.
- [28] Antony Galton and Matt Duckham. What is the region occupied by a set of points? In *GIScience*, 2006.
- [29] Yossi Gofman. Outline of a set of points. *Pattern Recognition Letters*, 14(1):31–38, 1993.
- [30] Christopher M. Gold. Data structures for dynamic and multidimensional gis. In *4th ISPRS Workshop on Dynamic and Multi-dimensional GIS*, pages 36–41, Pontypridd, Wales, UK, 2005.
- [31] D E Goldberg. *Genetic Algorithms in Search, Optimization, and Machine Learning*. Addison-Wesley, 1989.
- [32] Ronald L. Graham. An efficient algorithm for determining the convex hull of a finite planar set. *Inf. Process. Lett.*, 1(4):132–133, 1972.
- [33] Leonidas Guibas. Kinetic data structures. In D. Mehta and S. Sahni, editors, *Handbook of Data Structures and Applications*, pages 23–1–23–18. Chapman and Hall/CRC, 2004.
- [34] Leonidas Guibas, Menelaos Karaveles, and Daniel Russel. A computational framework for handling motion. In *Proceedings of the Sixth Workshop on Algorithm Engineering and Experiments*, pages 129–141, 2004.
- [35] Leonidas J. Guibas and Robert Sedgewick. A dichromatic framework for balanced trees. *Foundations of Computer Science, IEEE Annual Symposium on*, 0:8–21, 1978.
- [36] John Hersherberger and Subhash Suri. Convex hulls and related problems in data streams. In *Proceedings of ACM/DIMACS Workshop on Management and Processing of Data Streams*, pages 148–168, 2003.
- [37] Kathleen Hornsby and Max J. Egenhofer. Qualitative representation of change. In S. Hirtle and A. Frank, editors, *Spatial Information Theory: A Theoretical Basis for GIS, Proceedings of the International Conference COSIT'97*, pages 15–33. Springer-Verlag, 1997.
- [38] Yan Huang, Cai Chen, and Pinliang Dong. Modeling herds and their evolvments from trajectory data. In *GIScience '08: Proceedings of the 5th international conference on Geographic Information Science*, pages 90–105, Berlin, Heidelberg, 2008. Springer-Verlag.
- [39] R. A. Jarvis. On the identification of the convex hull of a finite set of points in the plane. In *Information Processing Letters*, volume 2, pages 18–21. North-Holland Publishing Company, 1973.
- [40] Jixiang Jiang and Michael Worboys. Detecting basic topological changes in sensor networks by local aggregation. In *Proceedings of the 16th ACM SIGSPATIAL international conference on Advances in geographic information systems, GIS '08*, pages 4:1–4:10, New York, NY, USA, 2008. ACM.

- [41] Jixiang Jiang, Michael Worboys, and Silvia Nittel. Qualitative change detection using sensor networks based on connectivity information. *GeoInformatica*, 15:305–328, 2011.
- [42] R Klette and A Rosenfeld. *Digital Geometry: Geometric Methods for Digital Picture Analysis*. Morgan Kaufmann, 2004.
- [43] Donald Knuth. *The Art Of Computer Programming: Sorting and Searching*, volume 3. Addison-Wesley, 2nd edition, 2007.
- [44] P. Laube, M. Van Kreveld, and S. Imfeld. Finding remo - detecting relative motion patterns in geospatial lifelines. In P. F. Fisher, editor, *Developments in Spatial Data Handling: Proceedings of the 11th International Symposium on Spatial Data Handling*, pages 201–214. Springer, 2004.
- [45] Patrick Laube, Matt Duckham, and Marimuthu Palaniswami. Deferred decentralized movement pattern mining for geosensor networks. *International Journal of Geographical Information Science*, 25(2):273–292, 2011.
- [46] Patrick Laube and Ross S. Purves. How fast is a cow? cross-scale analysis of movement data. *Transactions in GIS*, 15(3):401–418, 2011.
- [47] Mahmoud Melkemi. \mathcal{A} -shapes of a finite point set. In *Proceedings of the thirteenth annual symposium on Computational geometry*, SCG '97, pages 367–369. ACM, 1997.
- [48] Mahmoud Melkemi and Mourad Djebali. Computing the shape of a planar points set. *Pattern Recognition*, 33(9):1423 – 1436, 2000.
- [49] Mahmoud Melkemi and Mourad Djebali. Weighted \mathcal{A} -shape: a descriptor of the shape of a point set. *Pattern Recognition*, 34(6):1159 – 1170, 2001.
- [50] Adriano Moreira and Maribel Yasmina Santos. Concave hull: A k-nearest neighbours approach for the computation of the region occupied by a set of points. In *International Conference on Computer Graphics Theory and Applications GRAPP*, 2007.
- [51] David O’Sullivan and David J. Unwin. *Geographic Information Analysis*. Wiley, November 2002.
- [52] Mark H. Overmars and Jan van Leeuwen. Maintenance of configurations in the plane. *Journal of Computer and System Science*, 23(2):166–204, 1981.
- [53] Craig W. Reynolds. Flocks, herds and schools: A distributed behavioral model. In *Proceedings of the 14th annual conference on Computer graphics and interactive techniques*, SIGGRAPH '87, pages 25–34, New York, NY, USA, 1987. ACM.
- [54] P.L. Rosin. Measuring shape: ellipticity, rectangularity, and triangularity. In *Pattern Recognition, 2000. Proceedings. 15th International Conference on*, volume 1, pages 952 –955 vol.1, 2000.

- [55] P. H. Sneath. The application of computers to taxonomy. *J. Gen. Microbiol.*, 17:201–226, Aug 1957.
- [56] N. Srinivas and Kalyanmoy Deb. Multiobjective optimization using nondominated sorting in genetic algorithms. *Evolutionary Computation*, 2(3):221–248, 1994.
- [57] John G. Stell. Granularity in change over time. In M. Duckham, M. Goodchild, and M Worboys, editors, *Foundations of Geographic Information Science*, chapter 6, pages 95 – 115. Taylor and Francis, 2003.
- [58] Marius Thériault, Christophe Claramunt, and Paul Villeneuve. A spatio-temporal taxonomy for the representation of spatial set behaviours. In Michael Bhlen, Christian Jensen, and Michel Scholl, editors, *Spatio-Temporal Database Management*, volume 1678 of *Lecture Notes in Computer Science*, pages 1–18. Springer Berlin / Heidelberg, 1999.
- [59] J. Žunić and P.L. Rosin. A convexity measurement for polygons. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 26:173–182, 2002.
- [60] J. Žunić and P.L. Rosin. Rectilinearity measurements for polygons. *Pattern Analysis and Machine Intelligence, IEEE Transactions on*, 25(9):1193 – 1200, September 2003.
- [61] Zena Wood. *Detecting and Identifying Collective Phenomena within Movement Data*. PhD thesis, University of Exeter, 2011.
- [62] Zena Wood and Antony Galton. A taxonomy of collective phenomena. *Applied Ontology*, 4:267–292, August 2009.
- [63] Michael Worboys. Event-oriented approaches to geographic phenomena. *International Journal of Geographical Information Science*, 19:1–28, 2005.
- [64] Michael Worboys and Matt Duckham. *GIS: A Computing Perspective*, chapter 6.4 Point Object Structures, pages 240 – 248. CRC Press, 2nd edition, 2004.